



Ebinger Manufacturing Co

"The Race for Quality and Value Has No Finish Line"



Description: Heat Shrink Tubing

Multiple Wall – Adhesive Lined Polyolefin

Rated for continuous operation at temperatures from 67°F to +230°F

Shrink ratio is 2.5:1.

Tubing is radiation crosslinked with meltable adhesive liner

Complete waterproof insulation and provides resistance to abrasion, salt, and other corrosive materials.

Meets MIL-I-23053/4, Class 1.

10 PCS Per Bag

Status: Active

NAED#	Part#	Pre-Shrink ID	Wire Range	Length	Barcode#	Weight
00575	TUB1/8	1/8"	20-24	6"	718205005750	.10 LB
00576	TUB3/16	3/16"	22-18	6"	718205005767	.10 LB
00577	TUB1/4	1/4"	16-14	6"	718205005774	.10 LB
00578	TUB5/16	5/16"	12-10	6"	718205005781	.10 LB
00579	TUB3/8	3/8"	8-6	6"	718205005798	.20 LB
00580	TUB1/2	1/2"	4-2	6"	718205005804	.20 LB
00581	TUB3/4	3/4"	2, 1, 1/0	6"	718205005811	.40 LB
00582	TUB1	1"	2/0, 3/0, 4/0	6"	718205005828	.40 LB

For further technical information, please contact us.

Ebinger Manufacturing Co
7869 Kensington Ct.
Brighton, MI 48116

Hours: 8AM-5PM EST
Monday-Friday
Phone (248)486-8880
Fax (248)486-8080
emc48116@hotmail.com