



Ebinger Manufacturing Co
"The Race for Quality and Value Has No Finish Line"

Description: Wedge Anchors

Material: Zinc plated steel

Application: Used to support communications cables and other low voltage wires.

Available in machine screw or wood screw styles.

Status: Active



PART #	ANCHOR DIAMETER	MIN. EMBED.	INSTALLTION TORQUE (FT/LBS)	EMBEDMENT DEPTH	2000 PSI TENSION (LBS)	2000 PSI SHEAR (LBS)	4000 PSI TENSION (LBS)	4000 PSI SHEAR (LBS)
WA1/4X1-3/4	1/4"	1-1/8"	5-10	1-1/8"	1,841	1,443	2,408	1,813
WA1/4X2-1/4	1/4"	1-1/8"	5-10	1-3/4"	1,975	1,443	2,748	1,813
WA1/4X3-1/4	1/4"	1-1/8"	5-10	2-3/4"	1,975	1,443	2,748	2,748
WA3/8X2-1/4	3/8"	1-1/2"	25-30	1-1/2"	1,631	4,318	3,656	5,121
WA3/8X3	3/8"	1-1/2"	25-30	3"	3,229	4,318	6,328	5,121
WA3/8X3-3/4	3/8"	1-1/2"	25-30	3"	3,229	4,318	6,328	5,121
WA3/8X5	3/8"	1-1/2"	25-30	5"	4,075	4,318	6,328	5,121
WA1/2X2-3/4	1/2"	2-1/4"	50-60	2-1/4"	3,999	7,419	6,714	9,377
WA1/2X3-3/4	1/2"	2-1/4"	50-60	2-1/4"	3,999	7,419	6,714	9,377
WA1/2X4-1/4	1/2"	2-1/4"	50-60	4"	6,336	7,419	8,942	9,377
WA1/2X5-1/2	1/2"	2-1/4"	50-60	6"	6,902	7,419	8,942	9,377

For further technical information, please contact us.

Ebinger Manufacturing Co
7869 Kensington Ct.
Brighton, MI 48116

Hours: 8AM-5PM EST
Monday-Friday
Phone (248)486-8880
Fax (248)486-8080
emc48116@hotmail.com

Wedge Anchors

NAED #	PART #	Barcode #	Package QTY	Weight
01405	WA1/4X1-3/4	718205014059	100	3 LBS
01406	WA1/4X2-1/4	718205014066	100	4 LBS
01407	WA1/4X3-1/4	718205014073	100	5 LBS
01408	WA3/8X2-1/4	718205014080	100	8 LBS
01409	WA3/8X3	718205014097	100	10 LBS
01410	WA3/8X3-3/4	718205014103	100	12 LBS
01411	WA3/8X5	718205014110	50	16 LBS
01412	WA1/2X2-3/4	718205014127	50	18 LBS
01413	WA1/2X3-3/4	718205014134	50	24 LBS
01414	WA1/2X4-1/4	718205014141	25	28 LBS
01415	WA1/2X5-1/2	718205014158	25	32 LBS

For further technical information, please contact us.

Ebinger Manufacturing Co
7869 Kensington Ct.
Brighton, MI 48116

Hours: 8AM-5PM EST
Monday-Friday
Phone (248)486-8880
Fax (248)486-8080
emc48116@hotmail.com