



Ebinger Manufacturing Co
"The Race for Quality and Value Has No Finish Line"



Description: Sleeve Anchors. Dependable anchor for use in brick, cinder block, marble, and concrete. Sleeve anchor diameter and hole size are the same, simplifying installation. For anchoring door frames, aluminum and steel angles, steel columns, etc.

Material: Zinc Plated Carbon Steel

Status: Active

NAED#	Part#	ANCHOR DIAMETER	HOLE SIZE	BOLT DIAMETER	MIN. EMBED.	TORQUE FT/LB	2000 PSI TENSION (LB)	2000 PSI SHEAR (LB)	Barcode#	Package QTY	Weight
01416	SA1/4X1-3/8	1/4"	1/4"	3/16"	1-1/8"	5	875	1,430	718205014165	100	2.5 LBS
01417	SA1/4X2-1/4	1/4"	1/4"	3/16"	1-1/8"	5	875	1,430	718205014172	100	3.3 LBS
01418	SH5/16X1-1/2	5/16"	5/16"	1/4"	1-7/16"	8	1,110	2,145	718205014189	100	4.5 LBS
01419	SH5/16X2-1/2	5/16"	5/16"	1/4"	1-7/16"	8	1,110	2,145	718205014196	100	6.3 LBS
01420	SH3/8X1-7/8	3/8"	3/8"	5/16"	1-1/2"	15	1,590	3,060	718205014202	50	4 LBS
01421	SH3/8X3	3/8"	3/8"	5/16"	1-1/2"	15	1,590	3,060	718205014219	50	5.4 LBS
01422	SH3/8X4	3/8"	3/8"	5/16"	1-1/2"	15	1,590	3,060	718205014226	50	6 LBS
01423	SH1/2X2-1/4	1/2"	1/2"	3/8"	2-1/4"	25	3,145	4,975	718205014233	25	3.9 LBS
01424	SH1/2X3	1/2"	1/2"	3/8"	2-1/4"	25	3,145	4,975	718205014240	25	4.75
01425	SH1/2X4	1/2"	1/2"	3/8"	2-1/4"	25	3,145	4,975	718205014257	25	5.5

For further technical information, please contact us.

Ebinger Manufacturing Co
 7869 Kensington Ct.
 Brighton, MI 48116

Hours: 8AM-5PM EST
 Monday-Friday
 Phone (248)486-8880
 Fax (248)486-8080
 emc48116@hotmail.com